The Fronius storage solution

Reserva





Technical details

			Reserva 6.3	Reserva 9.5	Reserva 12.6	Reserva 15.8		
Electrical parameters	Usable capacity	kWh	6.31	9.47	12.63	15.79		
	Depth of discharge	%	94.5					
	Number of battery modules		2	3	4	5		
	Rated voltage	٧	204.8	307.2	409.6	512		
	Voltage range	٧	185.6 ~ 227.2	278.4 ~ 340.8	371.2 ~ 454.4	464 ~ 568		
	Maximum output current ¹	А	32					

	Battery cell chemistry		Lithium iron phosphate (LFP)					
	Parallel operation		Up to 4 batteries					
	Dimensions (height x width x depth)	mm	860 x 780 x 176	1,100 x 780 x 176	1,360 x 780 x 176	1,610 x 780 x 176		
	Total weight	kg	86.5	120	153.5	187		
	Compatible inverters		Fronius hybrid inverter ²					
ta	Protection class		IP65					
al da	Max. altitude above sea level	m	2,000					
General data	Ambient temperature range ³	°C	-20 to +55					
ဗွ	Permissible humidity	%	5 to 95					
	Installation		Indoor and protected outdoor areas					
	DC connection technology		4x Amphenol					
	Certificates and compliance with standards		IEC62619:2022; CE; VDE 2510-50; IEC62477-1; UN38.3					
	Interfaces		RS485					
	Warranty		10 years					

 $^{^{\}mbox{\scriptsize 1}}\mbox{\it The charging and discharging current is limited by the inverter.}$

² Except Fronius Symo Hybrid

³ Depending on the temperature, the charging/discharging capacity can be limited.

			вмѕ	Base	Module
Reserva Components	Usable capacity	kWh	-	-	3.15
	Rated voltage	٧	-	-	102.4
	Dimensions (height x width x depth)	mm	360 x 780 x 176	60 x 780 x 176	250 x 780 x 176
	Dimensions (with packaging)	mm	790 x 554 x 315		790 x 372 x 264
	Weight	kg	16	3.5	33.5
	Weight (with packaging)	kg	25		36.5



Technical details



The Fronius Reserva is an efficient DC-coupled high-voltage battery for storing solar energy with minimal losses. It can be flexibly expanded with two to five modules and is perfectly matched to Fronius hybrid inverters - for maximum performance. European data security and fast service ensure maximum reliability.





The heart of your PV system

With the Fronius GEN24 Plus, you can enjoy 24 hours of sun at home. The hybrid inverter allows you to connect a battery storage system, making you even more independent.





Backup power for every eventuality

With the Fronius Backup Controller & Backup Switch, you can switch to full backup power operation either automatically or manually. These cost-effective switching components can be installed in the control cabinet to save space and eliminate the need for additional hardware such as switch boxes.





Everything under control

With our Fronius Solar.web monitoring tool, you can keep an eye on your PV system any time, anywhere, keeping your energy transition on track, simply by using it in our app or on the web.

More information about the Fronius Reserva: www.fronius.com/en/reserva

Froniusplatz 1 4600 Wels Austria pv-sales@fronius.com www.fronius.com EN_without ECA Vo1 Feb 2025